



Номер подшипника	Размеры (мм)					Load Rating(KN)		Вес (кг)
	д	Д	Б	гмин	r1min	Динамический(Cr)	Статический (Cor)	
6000	10	26	8	0.3	/	A580	1.97	0.019
6001	12	28	8	0.3	/	5.11	2.39	0.021
6002	15	32	9	0.3	0.3	5.59	2.84	0.03
6003	17	35	10	0.3	0.3	6.01	3.25	0.04
6004	20	42	12	0.6	0.5	9.38	s030	0.068
60/22	22	44	12	0.6	0.5	9.41	5.12	0.074
6005	25	47	12	0.6	0.5	10.06	5.85	0.079
60/28	28	52	12	0.6	0.5	11.93	7.4	0.098
6006	30	55	13	1	0.5	13.23	8.3	0.113
60/32	32	58	13	1	0.5	13.25	8.38	0.129
6007	35	62	14	1	0.5	16.21	10.42	0.149
6008	40	68	15	1	0.5	17.03	11.7	0.185
6009	45	75	16	1	0.5	21.09	14.77	0.231
6010	50	80	16	1	0.5	22.02	16.25	0.25
6011	55	90	18	1.1	0.5	30.26	21.93	0.362
6012	60	95	18	1.1	0.5	31.66	24.22	0.385
6013	65	100	18	1.1	0.5	32.06	24.89	0.408
6014	70	110	20	1.1	0.5	38.59	30.43	0.573
6015	75	115	20	1.1	0.5	40.2	33.2	0.603
6016	80	125	22	1.1	0.5	47.5	39.8	0.821



Deep groove ball bearings 6000 series

6017	85	130	22	1.1	0.5	50.8	42.8	0.848
6018	90	140	24	1.5	0.5	58	49.8	1.103
6019	95	145	24	1.5	0.5	57.8	50	1.156
6020	100	150	24	1.5	0.5	64.5	56.2	1.174