



### Main dimensions

Номер подшипника	Main dimensions														Rated load(KN)		Weight(g)
	д	d3	Б	C1	W	h1	d2	L4	L5	d4	d5	d6	L3	α	Dynamic load (C)	Static load (C)	
SI5T/K	5	M5×0.8	8	6	9	27	18	36	4	8.5	11	11.11	10	13	5.7	6	16
SI6T/K	6	M6x1.0	9	6.75	11	30	20	40	5	10	13	12.7	12	13	7.2	7.65	22
SI8T/K	8	M8x1.25	12	9	14	36	24	48	5	12.5	16	15.875	16	14	11.6	12.9	47
SI10T/K	10	M10×1.5	14	10.5	17	43	28	57	6.5	15	19	19.05	20	13	14.5	18	77
SI10-1T/K	10	M10×1.25	14	10.5	17	43	28	57	6.5	15	19	19.05	20	13	14.5	18	77
SI12T/K	12	M12×1.75	16	12	19	50	32	66	6.5	17.5	22	22.225	22	13	17	24	100
SI12-1T/K	12	M12x1.25	16	12	19	50	32	66	6.5	17.5	22	22.225	22	13	17	24	100
SI14T/K	14	M14x2.0	19	13.5	22	57	36	75	B	20	25	25.4	25	16	24	31	160
SI14-1T/K	14	M14×1.5	19	13.5	22	57	36	75	B	20	25	25.4	25	16	24	31	160
SI16T/K	16	M16×2.0	21	15	24	64	40	84	8	22	27	28.575	28	15	28.5	39	220
SI16-1T/K	16	M16×1.5	21	15	24	64	40	84	B	22	27	28.575	28	15	28.5	39	220
SI18T/K	18	M18x1.5	23	16.5	27	71	44	93	10	25	31	31.75	32	15	42.5	47.5	320
SI20T/K	20	M20×1.5	25	18	30	77	50	102	10	27.5	34	34.925	33	14	42.5	57	420
SI22T/K	22	M22×1.5	28	20	32	84	54	111	12	30	38	38.1	37	15	57	68	540
SI25T/K	25	M24×2.0	31	22	36	94	60	124	12	33.5	42	42.85	42	15	68	85	720
SI28T/K	28	M27×2.0	35	24	41	103	66	136	14	37	46	47.6	51	15	86	107	820
SI30T/K	30	M30×2.0	37	25	41	110	70	145	15	40	50	50.8	51	17	88	114	1100
SI30-1T/K	30	M27×2.0	37	25	41	110	70	145	15	40	50	50.8	51	17	88	114	1100
SI35T/K	35	M36×2.0	43	28	50	125	81	165.5	17	46	58	57.1	56	16	101	206	1600
SI40T/K	40	M42×2.0	49	33	55	142	91	187.5	19	53	65	66.6	60	17	124	280	2400
SI50T/K	50	M48×2.0	60	45	65	160	117	218.5	23	65	75	82.5	65	12	308	485	5000